

## Vertical Autoclave/Steam sterilizers IVA-4030





Vertical Autoclave/Steam sterilizers IVA-4030 are floor standing self-contained sterilizer units that require no plumbing and operate from a standard single-phase power supply. Equipped with an effective air-cooling system for liquid sterilisation. This speeds cooling time by up to 40% compared to standard models. The Iris Vertical Autoclaves are available from 35 litres chamber capacity. All are built with castor wheels as standard making them easy to move.

The IVA-4030 is widely used for sterilisation applications in laboratory, hospitals, and clinics as well as for industrial sterilisation applications in biotechnology and pharmaceutical industries.

## **Technical Specification:**

Model	IVA-4030
Capacity (liters)	35L
Chamber Dimensions (mm)	318×450 mm
Operating Temperature (°C )	134°C
Adjustment of Temperature	105 to 134°C
Working Pressure	0.22Мра
Maximum Operating Pressure	0.23Mpa
Drying Time	1 to 300 minutes
Certifications/Conformance	CE And ECM
External Dimensions (w x d x h) mm	480X460×850 mm
Net Weight (kg)	42 kg
Gross Weight (kg)	56 kg
Power (W)	2500 W
Electrical Requirements	AC220V/ 50Hz
Catalogue No.	580550502

## **Technical Data:**

IVA-4030	IVA-4050	IVA-4075	IVA-4100	IVA-4120	IVA-4150	
35 L	50 L	75 L	100 L	120 L	150 L	
318×450 mm	340×550 mm	400×600 mm	440×650 mm	480×660 mm	510×740 mm	
Stainless Steel						
134°C						
?±1°C						
0.22 Mpa						
0.23 Mpa						
105°C to 134°C						
Touch Digital Display						
0 to 99 minutes						
CE And ECM						
2500 W	3000 W	4500 W	4500 W	6000 W	6000 W	
480X460×850 mm	520×520×980 mm	560×560×980 mm	590×590×1080 mm	600×640×1140 mm	670×690×1130 mm	
42 kg	50 kg	70 kg	85 kg	100 kg	110 kg	
56 kg	68 kg	90 kg	105 kg	125 kg	135 kg	
AC220V/50Hz						
580550502	580551002	580551502	580552002	580552502	580553002	
	35 L 318×450 mm 2500 W 480×460×850 mm 42 kg 56 kg	35 L 50 L 318×450 mm 340×550 mm  2500 W 3000 W 480X460×850 mm 520×520×980 mm 42 kg 50 kg 56 kg 68 kg	35 L 50 L 75 L  318×450 mm 340×550 mm 400×600 mm  Stain  1  7  0.:  105°C  Touch D  0 to 9  CE /  2500 W 3000 W 4500 W  480×460×850 mm 520×520×980 mm  42 kg 50 kg 70 kg  56 kg 68 kg 90 kg	35 L 50 L 75 L 100 L  318×450 mm 340×550 mm 400×600 mm 440×650 mm  Stainless Steel  134°C ?±1°C  0.22 Mpa  0.23 Mpa  105°C to 134°C  Touch Digital Display 0 to 99 minutes  CE And ECM  2500 W 3000 W 4500 W 4500 W  480×460×850 mm 520×520×980 mm 560×560×980 mm 590×590×1080 mm  42 kg 50 kg 70 kg 85 kg 56 kg 68 kg 90 kg 105 kg	35 L 50 L 75 L 100 L 120 L  318×450 mm 340×550 mm 400×600 mm 440×650 mm 480×660 mm  Stainless Steel  134°C ?±1°C  0.22 Mpa  0.23 Mpa  105°C to 134°C  Touch Digital Display  0 to 99 minutes  CE And ECM  2500 W 3000 W 4500 W 4500 W 6000 W  480×460×850 mm 520×520×980 mm 560×560×980 mm 590×590×1080 mm 600×640×1140 mm  42 kg 50 kg 70 kg 85 kg 100 kg  56 kg 68 kg 90 kg 105 kg 125 kg	

## Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States